

IntercomR29x

data sheet

Powered by Whoo

X916 at a Glance

Whoo

Intuitive UI
API
SDK
Network hosted
SIP Trunk hosted
WebRTC TURN/STEP
Device monitoring

System - Physical & Power

Size: 12.75x5.11x1.1 inches (HxWxD)
Body material: Aluminum
RAM / ROM: 2GB / 16GB
Display: 7" IPS LCD
Screen: 7" capacitive touch screen
Camera: 3 Megapixels, automatic lighting
Relay In/Out: 3/3
Installation: On-wall or In-wall
Water-proof & Dust-proof: IP65

Video

Resolution: up to 1080p
Maximum image transfer rate: 1080p -30fps
High intensity LEDs for picture lighting during dark hours



IntercomR29x data sheet

Powered by Whoo

Networking

10/100 Mbps Ethernet connection
DHCP Client or Static IP
Network-Time-Protocol

Door Entry Feature

Internal DPDT relay for controlling a door opener.
Relays controlled individually by DTMF tones or messages.

More Specs

Ethernet port: RJ45, 10/100Mbps adaptive

- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- IP/IK Level: IP65/ IK06
- Installation: Flush-mounted & Wallmounted
- Flush-mounted DIM:
324x130x60mm
- Wall-mounted DIM: 324x130x33mm
- Working Humidity: 10-90%
- Working Temperature: -20°C - +55°C





IntercomR29X data sheet

