



# Whoo Mobile Video Intercom

The smarter, safer, better way to access your front door.

## Physical & Power

- Size: 12.75x5.11x1.1 inches (HxWxD)
- Body material: Aluminum
- RAM / ROM: 2GB / 16GB
- Display: 7" IPS LCD
- Screen: 7" capacitive touch screen
- Camera: 3 Megapixels, automatic lighting
- Relay In/Out: 3/3
- Installation: On-wall or In-wall
- Water-proof & Dust-proof: IP65



## Video

- Resolution: up to 1080p
- Maximum image transfer rate: 1080p - 30fps
- High intensity LEDs for picture lighting during dark hours

## Networking

- 10/100 Mbps Ethernet connection
- DHCP Client or Static IP
- Network-Time-Protocol

## Door Entry Feature

- Internal DPDT relay for controlling a door opener
- Relays controlled individually by DTMF tones or messages
- Camera permanently operational, not just during calls
- White balance: auto
- Viewing angle: 120 °
- Minimum illumination: 1LUX (without LED illumination)

## More Specs

- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- IP/IK Level: IP65/ IK06
- Installation: Flush-mounted & Wall-mounted
- Flush-mounted DIM: 324x130x60mm
- Wall-mounted DIM: 324x130x33mm
- Working Humidity: 10-90%
- Working Temperature: -20°C - +55°C
- Storage Temperature: -40°C - +70°C

Primary Contact:

 [info@whoo.ai](mailto:info@whoo.ai)

 646.228.6341

